

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 0 978 751 A2

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
09.02.2000 Bulletin 2000/06

(51) Int. Cl.⁷: **G02C 7/02**

(21) Application number: **99306045.8**

(22) Date of filing: **29.07.1999**

(84) Designated Contracting States:
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE**
Designated Extension States:
AL LT LV MK RO SI

(30) Priority: **30.07.1998 US 126259**

(71) Applicant:
**JOHNSON & JOHNSON VISION PRODUCTS,
INC.
Jacksonville, Florida 32216-0995 (US)**

(72) Inventors:
• **Chipman, Russell A.
Salem, Virginia 24153 (US)**
• **Reardon, Patrick John
Roanoke, Virginia (US)**

(74) Representative:
**Mercer, Christopher Paul
Carpmaels & Ransford
43, Bloomsbury Square
London WC1A 2RA (GB)**

(54) **Progressive addition lenses**

(57) The present invention relates to ophthalmic lenses. In particular, the invention provides ophthalmic lenses with reduced astigmatism. The lenses are composed of a surface and a compensating surface, the surface geometries of which are defined by segments of a size suitable to be defined by a tenth order x,y polynomial with Zernike coefficients.

EP 0 978 751 A2

Description

Field of the Invention

- 5 **[0001]** The present invention relates to ophthalmic lenses. In particular, the invention provides ophthalmic lenses with reduced astigmatism.

Background of the Invention

- 10 **[0002]** The use of ophthalmic lenses for the correction of ametropia is well known. For example, progressive addition lenses ("PAL's") are used for the treatment of presbyopia. On the front, or convex, surface of a PAL, three zones are provided: a distance vision zone with a refractive power suitable for distance vision; a near vision, or add power, zone, with refractive power for near vision; and an intermediate zone between the distance and near zones, with a refractive power for intermediate distance vision.
- 15 **[0003]** Inherent in ophthalmic lenses, such as PAL's, is an astigmatism introduced or caused by one or more of the lens surfaces, or a lens astigmatism. In PAL's, for example, the design of the front lens surface typically is constrained by the need to provide a distance zone and an add zone of maximum width connected by the intermediate zone obeying the following conditions:

- 20 $f(x, y, z)$ is continuous:
 $\partial f(x, y, z)/\partial(x, y)$ is continuous: and
 $\partial^2 f(x, y, z)/\partial(x^2, y^2, xy)$ is continuous over all x, y, z .

- 25 **[0004]** Such a surface inevitably introduces an astigmatism into the lens. Generally, the back, or concave, lens surface of a lens is not used to compensate for the astigmatism introduced by the front surface and, in fact, may also contribute to the lens astigmatism. Rather, the back surface typically is a spherical or toric surface intended to combine with the front surface to provide the wearer's required prescription.

- 30 **[0005]** Any number of lens designs have been tried to reduce lens astigmatism. However, although the known designs provide some minimal decrease in the astigmatism, large areas in the lenses' peripheries still are unusable due to the astigmatism.

Brief Description of the Drawings

[0006]

- 35 FIG. 1 is a diagrammatic view of a front surface of a lens of the invention.
 FIG. 2 is a plan view of a compensating surface of a lens of the invention.
 FIG. 3 is a side view of one embodiment of the lens of the invention.
 FIG. 4 is a depiction of the radius distribution of the overall optical zone power if a front surface of a lens of the invention.
 40 FIG. 5 is a plan view of a compensating surface of a lens of the invention.
 FIG. 6 is a plan view of a compensating surface of a lens of the invention.

Description of the Invention and its Preferred Embodiments

- 45 **[0007]** The present invention provides lenses, as well as methods for their design and production, in which lens astigmatism, or the astigmatism caused by one or more surfaces of the lens, is reduced. For purposes of the invention, by "lens" or "lenses" is meant any ophthalmic lens including, without limitation, spectacle lenses, contact lenses, intraocular lenses and the like. Preferably, the lens of the invention is a spectacle lens and, more preferably, the spectacle lens is a progressive addition lens, or a lens in which one or more surfaces provide zones with refractive power suitable for distance, near and intermediate vision.

- 50 **[0008]** In the lenses of the invention, reduction of lens astigmatism is achieved by use of a compensating surface that compensates for the astigmatism introduced by the one or more of the other lens surfaces. By "compensate" is meant that the lens astigmatism is reduced by about 15 percent or greater, preferably about 25 percent or greater, more preferably about 35 percent or greater of the nominal add power, or desired add power, of the lens. In one embodiment, the invention comprises, consists essentially of, and consists of a lens having an astigmatism caused by at least one surface of the lens, the lens comprising, consisting essentially of, and consisting of a front surface and a compensating surface that compensates for the lens astigmatism.

[0009] The lenses of the invention may be made of any known material suitable for their construction. If the lens is of a homogeneous composition, meaning that the lens material is of a uniform refractive index, the compensating surface may be the back surface of the lens. For example, the lens may have a toroidal, aspheric compensating surface designed to compensate for the astigmatism introduced by the front lens surface.

[0010] Alternatively, the lens may be multilayered, the compensating surface between the front and back lens surfaces. Thus, in another embodiment the invention comprises, consists essentially of, and consists of a lens having an astigmatism caused by at least one surface of the lens, the lens comprising, consisting essentially of, and consisting of, a front surface, a back surface, and a compensating surface that compensates for the lens astigmatism. The back surface may be of any desired shape such as spherical, aspherical, cylindrical, or toroidal.

[0011] The lens of the invention is produced by the method comprising, consisting essentially of, and consisting of the steps of: a.) dividing a front surface of a lens into a first plurality of segments, each of the plurality of segments of a size suitable for a tenth order x, y polynomial with Zernike coefficients to define a geometry for each segment; b.) providing a compensating surface the compensating surface divided into a second plurality of segments of a size suitable for a tenth order x, y polynomial with Zernike coefficients to define a geometry for each segment; and c.) optimizing the compensating surface to reduce the lens astigmatism.

[0012] Although, the method for producing and designing the lens of the invention may be used to design any lens, the invention will find its greatest utility in lenses that have an astigmatism producing surface, such as PAL's. Generally, in PAL's, this surface will be the front surface, but may be the back surface as well.

[0013] The design process of the invention begins with a three dimensional description of the front surface by any method known in the art. The front surface may contain the curvatures required for a PAL and be divided into distance, near and intermediate vision zones, the intermediate vision zone having a gradual change in refractive power along an eye path from the distance to the near zone.

[0014] In the present invention, the front surface is divided, or segmented, into a number of segments, shown in Fig. 1 as 101 through 125. The geometry of each segment is defined in terms of a tenth order x, y polynomial with Zernike coefficients. The number of zones, or segments, is determined by dividing the total area of the surface by the maximum area that can be covered by each segment. One ordinarily skilled in the art will recognize that this maximum area, or segment size, will depend on the portion of the surface under consideration and as well as a consideration of the maximum area that can be adequately modeled using a single, tenth order x, y polynomial with Zernike coefficients. Thus, the maximum area of a segment may vary from, for example, the distance power zone to the intermediate zone.

[0015] The coefficients of each polynomial are computed to provide the desired power profile, to minimize astigmatism, and to provide sag, or depth, across segment boundaries, and the like. These coefficients may be computed by any known method, such as by using commercially available, optical design software.

[0016] Referring to Fig. 1, the x and y coordinate axes of the front surface are orthogonal to one another and tangent to the lens surface at their origins. The sag of the surface, z , is perpendicular to the x, y plane. The tenth order polynomial may be obtained by any known optimization process, such as the use of commercial optimization software. The precise polynomial will depend on the weights placed on the various constraints defining the boundary conditions of each optimization task. These boundaries include, without limitation, sag and slope continuities with neighboring zones, minimization of Zernike coefficients, variations in power, and the like. By placing a larger weight on any given constraint, optimization is directed towards that object. For example, a segment with decreased astigmatism may be obtained if the sag continuity constraint is reduced.

[0017] The sag mismatch, or discontinuity, between segments for the front surface of the lens of the invention preferably ranges from about 0 to about 0.01 microns. A total of twenty-five zones are used in Fig. 1 covering a circular area of 23 mm in radius.

[0018] Generally, the front surface is defined in terms of a base spherical surface with sufficient power to provide the desired distance vision correction. To the base sphere is added the sag corresponding to the additional power desired at each point. It is a discovery of the invention that the use of a polynomial of an order lower than the tenth provides a poor segment fit. Also, it is a discovery that polynomials of an order higher than the tenth are problematic in that they are difficult to optimize and require a greater number of computations.

[0019] A compensating surface is then provided. The compensating surface is divided into a number of segments as shown in Fig. 2. The number and geometry of the segments being determined as for the front surface.

[0020] The purpose of the compensating surface is to reduce the lens astigmatism to by about 15 percent or greater, preferably about 25 percent or greater, more preferably about 35 percent or greater of the nominal add power of the lens. The compensating surface is defined in terms of a base sphere and point by point departures from sphericity required for the compensation desired. The geometry of each segment of the compensating surface is defined by a tenth order x, y polynomial with Zernike coefficients determined as described for the front surface and using an optimization process, such as for example one that includes a ray tracing task choosing a certain pupil diameter, and then measuring the size and shape of the image on an image surface constructed before the optimization started. The compensating surface is then optimized so that the lens astigmatism is reduced. One ordinarily skilled in the art will recog-

nize that any number of optimization methods known in the art, as for example those disclosed in "General Optics and Optical Design" P. Pouroulis and J. MacDonald, Oxford Univ. Press (1997) incorporated herein by reference, may be used.

[0021] For example, trial functions may be combined with the front surface geometry and optimized to minimize the Zernike coefficients controlling the astigmatism. Optimization may be preformed by any known method, such as the use of optical design software and the assigning of appropriate weights to the Zernike coefficients that control astigmatism. Alternatively, the optimization is achieved by creating an image surface at the eye rotation point optimizing each compensating surface segment using a merit function that includes image quality or spot size at the image planes as well as the Zernike coefficients most directly controlling astigmatism.

[0022] Additional constraints also may be placed on the organization protocol, such as power as a function of x and y coordinates, and prism. The sag of each polynomial at the boundary of each segment may be such that a discontinuous or continuous compensating surface is formed. By discontinuous is meant that the sag mismatch between segments is about 2 micron or greater. By a continuous surface is meant that the mismatch is less than about 2 microns. Preferably, a continuous surface is used. Other constraints may be placed in order to ensure that the slopes of power, astigmatism, and prism are continuous across segment boundaries.

[0023] The compensating surface is designed to provide either or both aspheric radially symmetric and radially asymmetric corrections for the radially symmetric and radially asymmetric astigmatism of the front and/or back surface. Alternatively, the compensating surface is designed to provide aspheric radially asymmetric corrections and a back surface is used to provide the radially symmetric corrections.

[0024] In the lens of the present invention, if a toric correction is required in addition to the multifocal add power, the back surface of the lens must be placed with the toric axis at a specific angular orientation with respect to the umbilical meridional. In this case, the compensating surface cannot form the lens' back surface because, the back surface cannot provide compensation for lens astigmatism. Thus, in such cases, one or more compensating surfaces between the front and back surface provide all of the lens astigmatism compensation.

[0025] In an embodiment of the present invention, the compensating surface may form the back lens surface, prior to application of any coatings, provided that no toric correction is required. The compensating surface may also be provided with radially symmetric aspheric corrections to minimize spherical aberration and further improve image quality. One ordinarily skilled in the art will recognize that the shape of the compensating surface will be determined by whether that surface is being used as the back surface of the lens or a surface intermediate the front and back surface.

[0026] The back surface of the lens of the invention is provided by defining the surface in terms of two radii of curvatures, corresponding to the base and toric curves as well as a radial aspheric component that is defined in terms of a conic section. The back surface is designed using segments defined by tenth order x, y polynomials with Zernike coefficients, as in the case of the front and compensating surfaces. The base curve of the back surface is selected to provide the spherical correction required by the prescription. In addition to providing the correct spherical and toric powers, the back surface may be aspherized to provide higher order corrections of the Zernike coefficients, such as the third order correction for coma, or the fourth order correction for spherical aberration. It is known by those ordinarily skilled in the art that the quality of the retinal image is significantly affected by aberrations arising from higher order Zernike coefficients, in addition to the lower order coefficients controlling defocus and astigmatism.

[0027] The lens of the invention may be made by any convenient method. Preferably, the lens is made by fabricating a lens that has a front surface of a specified geometry and a compensating surface with the desired geometry. The optical material used to form the lens of the invention may be any melt processable thermoplastic resin, including without limitation a polycarbonate of bisphenol-A, or a thermoset resin, including without limitation diethylene glycol bisallyl carbonate. The material may be formed into a lens by any known method, such as injection, compression, or cast molded, or a combination thereof, using any convenient means of polymerization.

[0028] In the case in which a back surface is provided in addition to the compensating surface, the lens may be formed by any known method. Preferably, a preform, that is a front surface and a compensating surface with the desired geometries, is placed with its concave surface in juxtaposition with a toric mold the molding surface of which is designed to provide the desired back surface geometry, such as a toroidal, aspheric surface. The space between the preform and mold is filled with a polymerizable resin which is then polymerized to form a rigid, adherent layer permanently attached to the preform. The angular orientation between the principal meridian on the front surface and the toxic axis of the mold may be adjusted prior to initiating polymerization so that the toxic axis formed is at the desired orientation. In a preferred embodiment, the back surface provides only toxic correction, although one ordinarily skilled in the art will recognize that it is possible to add any desired geometry by adding surface castings to the back surface.

[0029] In an alternative embodiment of the invention, a layer is provided that is bounded by the front surface and the compensating surface that is fabricated of an optical material of a high refractive index, meaning of a refractive index of at least 1.57. Suitable materials include, without limitation, polycarbonate, thermoset materials incorporating high index monomers, such as styrenes, 4-vinyl anisole, divinyl benzene, acrylate and methacrylate terminated monomers containing aromatic moieties such as alkoxylated bisphenol-A mono- and diacrylate, acrylate terminated aromatic poly-

urethanes, aromatic epoxides, or thermoplastic materials such as aromatic polyethers, polysulfides, and polyetherimides. A second layer bounded by the compensating surface and the back lens surface is provided that is fabricated of a material with a refractive index of less than about 1.57. The efficiency of compensation provided by the compensating surface will depend on the difference of the refractive indices of the two layers. The departure from sphericity, as measured by sag required for compensation, increases with the difference in refractive indices of the layers. In the embodiment, some or all of the desired spherical power may be provided by the layer bound by the front and compensating surfaces and the toric power may be provided by the layer bound by the compensating and back surface. The difference in refractive indices used preferably is the maximum that is obtainable considering the material selected and the need to minimize interfacial reflection.

[0030] As an alternative embodiment of the lens of the invention, some or all of the compensation desired for the compensating surface may be incorporated into the front surface. The back surface is fabricated of a material having a refractive index of at least 1.57 allowing the reduction in the difference of refractive indices between the two layers to be less.

[0031] Such a lens may be formed by molding, casting, or grinding the front surface of an optical preform, the geometry of which provides some or all of the spherical and add power desired. The concave surface of the preform forms the compensating surface, which surface is molded, casted, or ground to provide the desired compensating geometry. The preform is of a material having at least a 1.57 refractive index. The back lens surface is formed on the preform by any convenient means, preferably by providing a mold and polymerizing a resin layer situated between the concave preform surface and the mold surface. The resin refractive index is selected so as to provide the desired difference in indices between the layer bound by the front and compensating surface and that bound by the compensating surface and the back surface of the lens.

[0032] In another alternative embodiment of the invention, one or more compensating surfaces are used to reduce the reflection from that surface and provide correction for chromatic aberration as shown in Fig. 3. Referring to Fig. 3, a front surface 31, a first compensating surface 32, and a second compensating surface 33 are provided. Back surface 34 provides toric correction. The material used for the second compensating layer 33 may be selected to have a chromatic dispersion opposite that of the material used for the first compensating layer 32. Suitable materials useful to correct for chromatic aberration are materials that incorporate chromophores strongly absorptive at near infra-red wavelengths while having little or no optical absorption in the visible wavelength range. Examples of such materials include, without limitation, naphthalocyanins exhibiting strong ligand field absorption in the 900 to 1000 nm range and d_2 to d_4 metal complexes with near infra-red ligand field absorptions, e.g., Fe^{2+} , Co^{2+} , Ni^{2+} chelates, and the like. Preferably, more than one compensating surface is used to correct for chromatic aberration.

[0033] In yet another alternative, the constraint providing sag continuity between adjacent segments of the compensating surface may be selectively removed in order to further reduce astigmatism in the segments. It is important to ensure that the resulting sag discontinuity does not introduce an unacceptable level of prism jump by adjusting the weights attached to the minimization of the prism discontinuity during the optimization process until the discontinuity is equal to or less than about 0.5 diopters.

[0034] In yet another embodiment, one or more compensating surfaces are used, all of which surfaces are continuous, discontinuous, or a mixture thereof. In still another embodiment, the compensating surfaces each are composed of continuous and discontinuous portions.

[0035] The invention will be clarified further by a consideration of the following, non-limiting examples.

Examples

Example 1

[0036] A front surface of a lens of the invention was designed by dividing a 23 mm diameter surface is divided as shown in Fig 1 into twenty-five segments, 101 through 125. Each segment was defined in terms of the tenth order, Zernike polynomial set forth on Table 1. The weights attached to the minimization of sag discontinuity at the segments' borders were adjusted until the sag discontinuity was 0.01 microns. On Table 1 is listed the coefficients of the tenth order polynomial used to fit segment 101. In Fig. 4 is shown the radius distribution over the overall optical zone of the front surface. Code V, a commercially available optical design software available from Optical Research Associates, Pasadena California, was used to model the optical performance of this optic and scale the sag values as needed in order to change the magnitude of the add power from 2.00 diopters to 1.75 diopters.

Table 1

Term	Coefficient	Term	Coefficient	Term	Coefficient
X	2.9959E-04	X ⁴ Y ²	-1.3287E-08	X ⁹	-5.7194E-14
Y	1.3627E-02	X ³ Y ³	3.2104E-09	X ⁸ Y	-1.1805E-13
X ²	-3.2144E-04	X ² Y ⁴	-2.1453E-08	X ⁷ Y ²	-1.3143E-13
XY	-2.6844E-05	XY ⁵	1.6867E-08	X ⁶ Y ³	2.1387E-13
Y ²	-2.2985E-04	Y ⁶	-1.1813E-09	X ⁵ Y ⁴	2.9089E-14
X ³	-1.2719E-06	X ⁷	3.1168E-11	X ⁴ Y ⁵	-1.2660E-13
X ² Y	-4.6118E-05	X ⁶ Y	1.5823E-10	X ³ Y ⁶	-2.1756E-14
XY ²	2.8283E-06	X ⁵ Y ²	1.4535E-11	X ² Y ⁷	-1.0163E-14
Y ³	-2.3678E-05	X ⁴ Y ³	1.7491E-10	XY ⁸	-1.3631E-13
X ⁴	-4.6537E-07	X ³ Y ⁴	4.0348E-12	Y ⁹	3.6008E-13
X ³ Y	-3.9656E-07	X ² Y ⁵	7.3962E-10	X ¹⁰	4.6851E-15
X ² Y ²	5.6116E-06	XY ⁶	7.6436E-11	X ⁹ Y	2.8582E-14
XY ³	-1.5922E-07	Y ⁷	-1.8914E-10	X ⁸ Y ²	1.0258E-14
Y ⁴	9.4637E-07	X ⁸	-5.1259E-12	X ⁷ Y ³	1.1640E-14
X ⁵	-1.3593E-09	X ⁷ Y	-1.4894E-11	X ⁶ Y ⁴	-5.3647E-14
X ⁴ Y	1.2154E-07	X ⁶ Y ²	-1.2730E-11	X ⁵ Y ⁵	2.8809E-14
X ³ Y ²	1.3703E-09	X ⁵ Y ³	-1.0932E-11	X ⁴ Y ⁶	-4.3787E-15
X ² Y ³	-1.1170E-07	X ⁴ Y ⁴	5.0458E-11	X ³ Y ⁷	3.9563E-14
XY ⁴	-1.9973E-08	X ³ Y ⁵	-1.8795E-11	X ² Y ⁸	-5.3160E-14
Y ⁵	4.2527E-08	X ² Y ⁶	4.7034E-11	XY ⁹	4.0808E-15
X ⁶	2.1750E-09	XY ⁷	-5.5050E-12	Y ¹⁰	6.3549E-15
X ⁵ Y	3.3402E-09	Y ⁸	-1.3198E-12		

Example 2

[0037] Fig. 5 illustrates the x and y coordinates of the segments that constitute a compensating surface of the invention. Segment 51 contains the optical center of the optic and is the channel with a blend zone to the spherical section. Segment 52 is the distance zone and is left spherical. Segment 51 is described by the tenth order polynomial set forth on Table 2 obtained by optimizing this segment for minimum astigmatism and best image quality at an image surface as described above. The optimization protocol assigned specified weights to sag constraints at the top, y= 10.0, line, second order derivatives using the continuity conditions shown on Table 1, Zernike coefficients, and the spot size of the image formed at the image surface. The sag discontinuity with the channels segment 602 was maintained to a value of 0.01 microns. On Table 2 is listed the coefficients of the polynomial developed to describe segment 53. The wings, segments 54 and 55, are tenth order polynomials optimized with sag, slopes, Zernike coefficients and spot size at the image surface.

Table 2

Term	Coefficient	Term	Coefficient	Term	Coefficient
X ⁰	4.0730E-03	X ¹	-1.1190E-03	X ²	-1.7264E-03
X ³	-1.1712E-04	X ⁴	-1.2035E-04	X ⁵	3.5938E-05

Table 2 (continued)

Term	Coefficient	Term	Coefficient	Term	Coefficient
X^6	4.4477E-06	X^7	2.9691E-07	X^8	1.1208E-08
X^9	2.2584E-10	X^{10}	1.8916E-12	Y	-5.9233E-02
XY	-1.0295E-02	X^2Y	-1.1153E-03	X^3Y	-4.9870E-07
X^4Y	-1.1567E-04	X^5Y	-1.1316E-05	X^6Y	-8.3565E-07
X^7Y	-3.0455E-08	X^8Y	-5.9808E-10	X^9Y	-4.9098E-12
Y^2	-1.0978E-04	XY^2	-9.1776E-05	X^2Y^2	1.9888E-05
X^3Y^2	1.3878E-05	X^4Y^2	2.6856E-06	X^5Y^2	2.4296E-12
X^6Y^2	1.1505E-08	X^7Y^2	2.4296E-10	X^8Y^2	2.7402E-07
Y^3	5.9516E-05	XY^3	-9.1729E-07	X^2Y^3	-3.9879E-05
X^3Y^3	-6.1659E-06	X^4Y^3	-4.9074E-07	X^5Y^3	-2.1523E-08
X^6Y^3	-4.9346E-10	X^7Y^3	-4.6135E-12	Y^4	-2.7018E-06
XY^4	-1.0059E-06	X^2Y^4	-1.8065E-7	X^3Y^4	-7.8954E-09
X^4Y^4	1.0659E-06	X^5Y^4	1.4961E-11	X^6Y^4	2.7573E-13
Y^5	-1.3605E-06	XY^5	-4.998E-07	X^2Y^5	-5.169E-08
X^3Y^5	-2.9916E-09	X^4Y^5	-8.5253E-11	X^5Y^5	-9.2168E-13
Y^6	-2.1353E-09	XY^6	-6.8412E-09	X^2Y^6	5.5626E-10
X^3Y^6	-2.0654E-11	X^4Y^6	-3.1664E-13	Y^7	-3.6560E-10
XY^7	-8.5806E-12	X^2Y^7	-4.2276E-13	X^3Y^7	9.0083E-14
X^8	-1.3447E-11	XY^8	8.6794E-13	X^2Y^8	3.0496E-14
Y^9	-5.3970E-14	XY^9	-5.0927E-15	Y^{10}	-2.0114E-14

Example 3

[0038] In Fig. 6 is shown a discontinuous compensating surface of the invention, or surface with a sag discontinuity exceeding about 2 microns. The spherical zone is represented by segment 601 and channel 602, having an upper blend zone. The 601 segment is spherical and the 602 segment is described by a tenth order polynomial obtained by optimizing this segment for minimum astigmatism and best image quality at an image surface. The optimization protocol assigned specified weights to sag constraints at the top, $y = 10.0$ line, second order derivatives the continuity conditions of which are as described in Table 1, Zernike coefficients, and the spot size of the image formed at the image surface. Similarly, the add power zone segment 603 was described by a tenth order polynomial maintaining the sag discontinuity with the channel segment 602 to below the value of 0.01 microns. The wings, 604 and 613, are horizontal strips optimized with weight on the sag constraint, allowing the sag discontinuity to rise to a maximum specified value of 15 microns, while constraining the first derivatives as well as the second derivatives and the Zernike coefficients. The weight on prism continuity is relaxed to allow prism discontinuity up to a maximum level of 0.25 diopters.

Claims

1. A lens having an astigmatism caused by at least one surface of the lens, the lens comprising a front surface and a compensating surface wherein the compensating surface compensates for the lens astigmatism.
2. The lens of claim 1 wherein the compensating surface is a continuous surface.
3. The lens of claim 1 wherein the compensating surface is a discontinuous surface.
4. The lens of claim 1 wherein the compensating surface comprises a plurality of segments.

5. The lens of claim 4 wherein each of the plurality of segments is defined by a tenth order x, y polynomial with Zernike coefficients.

6. The lens of any one of claims 1 to 5 further comprising at least one additional compensating surface.

7. The lens of claim 8 wherein at least one of the additional compensating surfaces is a discontinuous surface.

8. A progressive addition spectacle lens having an astigmatism caused by at least one surface of the lens, the lens comprising a front surface and a discontinuous compensating surface comprising a plurality of segments wherein each of the segments is defined by a tenth order x, y polynomial with Zernike coefficients.

9. A progressive addition spectacle lens having an astigmatism caused by at least one surface of the lens, the lens comprising a front surface and a continuous compensating surface comprising a plurality of segments wherein each of the segments is defined by a tenth order x, y polynomial with Zernike coefficients.

10. A method for providing a lens comprising the steps of:

a) dividing a front surface of a lens into a first plurality of segments, each of the plurality of segments being of a size suitable for a tenth order x, y polynomial with Zernike coefficients to define the geometry for each segment;

b) providing a compensating surface, the compensating surface being divided into a second plurality of segments of a size suitable for a tenth order x, y polynomial with Zernike coefficients to define a geometry for each segment; and


(c) optimizing the compensating surface to reduce a lens astigmatism of the lens.

Figure 3

25 Zone Front Surface Layout

116	115	114	113	112	y=23mm
117	105	104	103	111	y=16mm
					y=12mm
118	106	101	102	110	y=12mm
119	107	108	109	125	y=16mm
120	121	122	123	124	y=23mm
x=23mm	x=16mm	x=12mm	x=12mm	x=16mm	x=23mm

Figure 2






FIGURE 3

Figure 4

25 Zone Front Surface Mean Radius
Contour Map - (mm radius)



Figure 5





Fig 6



(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 0 978 751 A3

(12)

EUROPEAN PATENT APPLICATION

(88) Date of publication A3:
19.12.2001 Bulletin 2001/51

(51) Int Cl.7: **G02C 7/02**

(43) Date of publication A2:
09.02.2000 Bulletin 2000/06

(21) Application number: **99306045.8**

(22) Date of filing: **29.07.1999**

(84) Designated Contracting States:
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE**
Designated Extension States:
AL LT LV MK RO SI

(30) Priority: **30.07.1998 US 126259**

(71) Applicant: **JOHNSON & JOHNSON VISION
PRODUCTS, INC.**
Jacksonville, Florida 32216-0995 (US)

(72) Inventors:
• **Chipman, Russell A.**
Salem, Virginia 24153 (US)
• **Reardon, Patrick John**
Madison, Alabama 35758 (US)

(74) Representative: **Mercer, Christopher Paul**
Carpmaels & Ransford 43, Bloomsbury Square
London WC1A 2RA (GB)

(54) **Progressive addition lenses**

(57) The present invention relates to ophthalmic lenses. In particular, the invention provides ophthalmic lenses with reduced astigmatism. The lenses are com-

posed of a surface and a compensating surface, the surface geometries of which are defined by segments of a size suitable to be defined by a tenth order x,y polynomial with Zernike coefficients.

EP 0 978 751 A3



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 99 30 6045

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	US 5 771 089 A (BARTH RUDOLF) 23 June 1998 (1998-06-23) * column 3, line 10 - line 46 *	1,2,6,10	602C7/02
X	US 5 335 026 A (KATO KAZUTOSHI ET AL) 2 August 1994 (1994-08-02) * column 1, line 57 - column 2, line 22 *	1,2,10	
X	EP 0 809 126 A (SEIKO EPSON CORP) 26 November 1997 (1997-11-26) * column 6, line 53 - column 7, line 37 *	1,2,10	
A	WO 98 12590 A (ESSILOR INT ;BAUDART THIERRY (FR); LALOUX THIERRY (FR); PEDRONO CL) 26 March 1998 (1998-03-26) * page 17, line 25 - page 18, line 15 *	1,5,10	
			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
			G02C
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 26 October 2001	Examiner Sarneel, A
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

EPO FORM 1503 (3.82) (P04001)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 99 30 6045

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

26-10-2001

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
US 5771089	A	23-06-1998	DE	3430334 A1	27-02-1986
			AT	40222 T	15-02-1989
			AT	47630 T	15-11-1989
			AU	612283 B2	04-07-1991
			AU	4162489 A	04-01-1990
			AU	574226 B2	30-06-1988
			AU	4770985 A	07-03-1986
			AU	4771385 A	07-03-1986
			DE	3567744 D1	23-02-1989
			DE	3573953 D1	30-11-1989
			WO	8601308 A1	27-02-1986
			WO	8601309 A1	27-02-1986
			EP	0191831 A1	27-08-1986
			EP	0193552 A1	10-09-1986
			JP	62500122 T	16-01-1987
			JP	2618622 B2	11-06-1997
			JP	62500403 T	19-02-1987
			US	4955712 A	11-09-1990
US 5335026	A	02-08-1994	JP	3013396 B2	28-02-2000
			JP	4045419 A	14-02-1992
			JP	4195019 A	15-07-1992
			DE	69113127 D1	26-10-1995
			DE	69113127 T2	21-03-1996
			EP	0461624 A1	18-12-1991
			US	5270746 A	14-12-1993
			JP	4356011 A	09-12-1992
EP 0809126	A	26-11-1997	EP	0809126 A1	26-11-1997
			US	6019470 A	01-02-2000
			EP	0809127 A1	26-11-1997
			WO	9719382 A1	29-05-1997
			WO	9719383 A1	29-05-1997
			US	5926250 A	20-07-1999
WO 9812590	A	26-03-1998	FR	2753805 A1	27-03-1998
			AU	729511 B2	01-02-2001
			AU	4212197 A	14-04-1998
			BR	9711399 A	17-08-1999
			EP	0927377 A1	07-07-1999
			WO	9812590 A1	26-03-1998
			JP	2001503155 T	06-03-2001

EPO FORM P449

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

THIS PAGE BLANK (USPTO)